



STREET LIGHTING NOTES

- A.** 1 1/2" PVC CONDUIT SHALL BE INSTALLED WITH NO. 10/3 VF CABLE BETWEEN EACH POLE AND TO THE ELECTRIC FEED.
- B.** LIGHT POLE BASES SHALL BE AS THE DETAILS INCLUDED IN THESE STANDARDS.
- C.** LIGHT POLES SHALL BE ROUND, STRAIGHT, 18' IN HEIGHT, AND PAINTED BLACK MODEL NUMBER 18RRS.
- D.** LIGHT POLES SHALL BE LOCATED AT ALL INTERSECTIONS AND SPACED NO FURTHER THAN 140' APART. LIGHTING LAYOUT SHALL BE APPROVED BY THE VILLAGE PRIOR TO CONSTRUCTION.
- E.** FIXTURES SHALL BE HADCO, 175 WATT METAL HALIDE, MODEL NUMBER VH-60-AK2NQE, 120 VOLT, POST-TOP MOUNT LUMINAIRE WITH CLEAR LENS AND BLACK IN COLOR.
- F.** FIXTURE, SPACING, AND COLOR MAY VARY ACCORDING TO LOCATION AND SHALL BE APPROVED BY THE VILLAGE.

TRAFFIC CONTROL DEVICE NOTES

- A.** ALL TRAFFIC CONTROL DEVICES SHALL BE PER THE LATEST REVISION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS AND APPROVED BY THE VILLAGE BEFORE INSTALLATION.
- B.** ALL SIGN POST SHALL BE STANDARD STEEL POST UNLESS OTHERWISE APPROVED BY THE VILLAGE.
- C.** ALL STREET NAME SIGNS SHALL BE WHITE IN COLOR WITH BLACK LETTERING UNLESS OTHERWISE APPROVED BY THE VILLAGE.

REVISIONS:

DATE
APPROVED:
MAY 1997

PAGE No.

500-1